

DV-BP-CHRG

PLATINUM® FLEX LITHIUM-ION BATTERY CHARGER

OPERATING INSTRUCTIONS

READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT.

- 1) Check the charger, cable, and plug for damage before using. If damage is noticed, do not use the charger.
 - 2) Only charge JB Industries 18v Lithium-Ion batteries.
 - 3) Use/charge battery packs when the temperature is between 41°F (5°C) and 104°F (40°C).
 - 4) Keep the charger clean and free of debris.
 - 5) Do not touch the un-insulated terminals on the charging connector or short the terminals together. This can cause a fire or electric shock.
 - 6) Do not operate charger on flammable surfaces or near combustible items.
 - 7) Disconnect the charger from the power outlet when not in use.
 - 8) Protect the charger from heat sources, direct sunlight, and fire.
 - 9) Protect the charger from water, rain, and snow. Water increases the risk of electrical shock and damage to the charger. The charger should only be used indoors. Do not charge the battery in a damp or wet location.
 - 10) Do not disassemble the charger.
 - 11) Properly dispose of a damaged charger according to federal, state, and local regulations.
- 2) Slide the battery into the charging connector and observe indicator lights.
 - a. If the charger has a flashing red/green light, there is a problem with the battery or charger. Unplug the charger and disconnect the battery. Have the battery and charger inspected and/or repaired by qualified personnel.
 - b. If the charger has a flashing red light, disconnect the battery. The battery is too hot and must cool down first before charging.
 - c. If the charger has a solid red light, the battery is charging.
 - d. If the charger has a solid green light, the battery is charged.
 - 3) When charging is complete, remove the battery and unplug the charger.



WARNING: Improper use can lead to fire hazard, death or serious injuries.

LED INDICATOR LIGHT FUNCTIONS

Solid Green	= Standby/battery fully charged
Solid Red	= Charging
Flashing Red	= Temperature fault (battery is too hot)
Flashing Red/Green	= Defective charger or battery

The information contained in this manual is provided for informational purposes only. The information and recommendations are in good faith and are believed to be accurate as of the date of printing. However, JB INDUSTRIES MAKES NO WARRANTY, EITHER EXPRESSED OR IMPLIED, WITH RESPECT TO THIS INFORMATION AND DISCLAIMS ALL LIABILITY FROM RELIANCE ON IT.



JB INDUSTRIES
800.323.0811 JBIND.COM SALES@JBIND.COM