



AURORA LD-6000IR

INFRARED LEAK DETECTOR

FEATURES

- Detects all CFC, HFC, HCFC, HFO-1234YF and blended refrigerants
- Infrared sensor life > 10 years
- High (0.10 oz/year and higher), medium (0.25 oz/year and higher), and low (0.5 oz/year and higher) sensitivity settings
- Visual and audible alerts
- Accurate to 0.10oz/year
- Won't trigger on oil or moisture
- Convenient magnetic hanger
- Easy-to-read LED display
- Stores highest change in refrigerant concentration achieved
- Protective carrying case
- Magnetic hanger
- 8 hour rechargeable lithium ion battery
- 1 year warranty

PART NO.	DESCRIPTION
LD-6000IR	AURORA leak detector in case
LDA-WE9	Wand extension – 9"
LDA-NNP4	Needle nose probe – 4-3/4"
LDA-NNP9	Needle nose probe – 9"
LDA-VCH	12v vehicle charger
LDA-WCH	120-240v wall charger
LDA-WCHUS	Wall charger – US connector (also available for UK, EU)
LDA-LI	3.7v Lithium ion battery 1800 mAh
LDA-WTP	Wand tip
LDA-PK	Filters (10) for wand tip and probes plus o-rings (5)



SENSITIVITY

R1234yf
R22
R134a
R404A
R407A
R410A
R427A
R502

