



## **M2-HP HEAT PUM**


## 2-VALVE FORGED BRASS MANIFOLD

## **FEATURES**

- Full flow free floating dual o-ring sealing system design for faster evacuation and charging
- Forged brass bar with angled bar for increased knuckle clearance to rotate handwheels
- Includes Illuminating, Class 1, 1% metal gauges designed for 800psi to handle heat pump pressures
- Pressure/temperature scale has two sections to accommodate temperature glide on R407c
- Available with KOBRA® high pressure black hoses
- Replaceable, durable hanging hook and intake/hose holder fittings
- 1 year warranty; lifetime on bar

## **ORIGINAL FREE FLOATING DUAL O-RING SEALING SYSTEM**

Stem seats retract completely for full flow path



Zero leakage high pressure raised seat for positive seating

	W.
ago so	100 400 150 mm 140 150
Hall to the state of the state	8
	600 600 600 600 600 600 600 600 600 600
	600 600 600 600 600 600
A STATE OF S	AND
130 130 PA 100 P	800 ps

- N	. /	n		г
- 1	VI	2-	п	ь
•		_		

	R22	R407C	410A	
	PART NO.	HOSES	GAUGE SIZE	GAUGE FEATURES
	M2-HP	Manifold Only	3-1/8" (80mm)	Illuminating,Class 1, 1%
ĺ	M2-HP-5	CL6-60" (3)	3-1/8" (80mm)	Illuminating,Class 1, 1%
	M2-808	Replacement Gauge	3-1/8" (80mm)	Illuminating,Class 1, 1%











