

PLATINUM

FLEX



AC & BATTERY POWERED VACUUM PUMP

AMERICAN-MADE FOR MAXIMUM MOBILITY.

- Powered by 9.0Ah/18V lithium-ion battery or auto-switching dual voltage AC Adapter (sold separately)
- Compatible with multiple battery brands, including Milwaukee®, DeWalt®, and JB
- 1/2 HP brushless DC motor
- Fully A2L-compatible for next-generation systems
- All-metal construction with USA-sourced materials, brass fittings, and stainless-steel valving
- Low battery warning light with audible alert
- 15 micron vacuum rating for fast pull-down performance
- Gas ballast and blank-off isolation valve
- Ergonomic 1/2" NPT exhaust handle with lift ring
- Large, easy-to-read oil level sight glass with easy access oil fill located on cover
- O-ring sealed oil drain valve to prevent leaks and tethered safety cap to prevent oil spills
- Internal check valve prevents oil back-flow during power failure
- Field repairable
- 1-year OTC Warranty; 2-year on vacuum pump



DV-BP-BAT



DV-BP-CHRG



DV-BP-AC



PLATINUM® FLEX VACUUM PUMPS				
	DV-85-FLEX-CORE	DV-142-FLEX-CORE	DV-85-FLEX	DV-142-FLEX
CFM	3 CFM (85 l/m)	5 CFM (142 l/m)	3 CFM (85 l/m)	5 CFM (142 l/m)
MOTOR	1/2 HP, 1725 RPM	1/2 HP, 1725 RPM	1/2 HP, 1725 RPM	1/2 HP, 1725 RPM
VOLTAGE	Battery: 9.0 Ah/18V Adapter: 115v/60Hz 230v/50Hz	Battery: 9.0 Ah/18V Adapter: 115v/60Hz 230v/50Hz	Battery: 9.0 Ah/18V Adapter: 115v/60Hz 230v/50Hz	Battery: 9.0 Ah/18V Adapter: 115v/60Hz 230v/50Hz
INTAKE PORT	1/2" x 1/4" x 3/8"	1/2" x 1/4" x 3/8"	1/2" x 1/4" x 3/8"	1/2" x 1/4" x 3/8"
OIL CAPACITY	26oz (769cc)	21oz (621cc)	26oz (769cc)	21oz (621cc)
BATTERY RUN TIME	Approx. 90 min.	Approx. 60 min.	Approx. 90 min.	Approx. 60 min.
INCLUDED	Pump Only	Pump Only	Battery, Charger and AC Adapter	Battery, Charger and AC Adapter

Accessories

Accessories shown above are available in pump kits or sold separately.

POWER TO GO. ANYWHERE.



FOLLOW US!
f in y o i g

JB INDUSTRIES
800.323.0811 JBIND.COM SALES@JBIND.COM